



# ICE CONTROL EQUIPMENT

## SPECIFICATIONS



Striker™ STAINLESS STEEL HOPPER SPREADERS				AVAILABLE POWER OPTIONS & APPROX. WEIGHT (EMPTY)								
Body Side Length	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Dual 12V DC Sealed Motors	Gas 10.5 hp I/C Briggs & Stratton®	Gas 11 hp I/C Honda®	Dual Hydraulic Motors	Conveyor Width	Spinner Size	Spreading Width	Materials	Vehicle Application
7'	1.5 cu yd	16 ga SS	84" x 50" x 38"	595 lb	—	—	—	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Trucks
8'	2.0 cu yd	16 ga SS	96" x 50" x 40"	615 lb	740 lb	740 lb	615 lb	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Pickup Trucks
9'	3.0 cu yd	16 ga SS	108" x 50" x 41"	695 lb	820 lb	820 lb	695 lb	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)
9'	4.5 cu yd	16 ga SS	108" x 70" x 47"	815 lb	940 lb	940 lb	815 lb	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)
10'	4.5 cu yd	16 ga SS	120" x 70" x 47"	—	965 lb	965 lb	840 lb	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)
10'	6.0 cu yd	16 ga SS	120" x 70" x 54"	—	1010 lb	1010 lb	885 lb	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)

Tornado™ POLY/ELECTRIC HOPPER SPREADERS				AVAILABLE POWER OPTIONS & APPROX. WEIGHT (EMPTY)								
Body Side Length	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Dual 12V DC Sealed Motors	Gas 10.5 hp I/C Briggs & Stratton®	Gas 11 hp I/C Honda®	Dual Hydraulic Motors	Conveyor Width	Spinner Size	Spreading Width	Materials	Vehicle Application
7'	1.5 cu yd	Polyethylene	108" x 63" x 44"	591 lb	—	—	—	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Pickup Trucks
8'	1.8 cu yd	Polyethylene	117" x 63" x 44"	660 lb	—	—	—	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Pickup Trucks
8'	2.5 cu yd	Polyethylene	117" x 63" x 51"	734 lb	—	—	—	16½"	15½"	Up to 40'	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)

Tornado LT™ POLY HOPPER SPREADER				AVAILABLE POWER OPTIONS & APPROX. WEIGHT (EMPTY)								
Body Side Length	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Dual 12V DC Sealed Motors	Gas 10.5 hp I/C Briggs & Stratton®	Gas 11 hp I/C Honda®	Dual Hydraulic Motors	Conveyor Width	Spinner Size	Spreading Width	Materials	Vehicle Application
5½'	0.5 cu yd	Polyethylene	77" x 48½" x 27"	386 lb	—	—	—	—	12"	Up to 40'	Salt or 50/50 Salt/Sand Mix	UTVs & Pickup Trucks

TAILGATE SPREADERS												
Model	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Approximate Weight (empty)	Electric Motor	Auger (Diam. x Length)	Spinner Size	Spreading Width	Materials	Vehicle Application	Available Mounts	
PRO-FLO™ 525	5.25 cu ft	Polyethylene	20½" x 38" x 34"	160 lb	Dual, 12-volt 1/3 hp	3" x 14" Heavy-Duty Solid Steel	10"	Up to 30'	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, SUVs, 1-Ton or Smaller Pickups	Standard 2" Receiver, 3-point Combo Mount	
PRO-FLO™ 900	9.00 cu ft	Polyethylene	24" x 52" x 36"	180 lb	Dual, 12-volt 1/3 hp	3" x 20" Heavy-Duty Solid Steel	12"	Up to 40'	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, 1-Ton or Smaller Pickups	Pivot Mount, 2" Receiver Hitch (requires adapter mount), 3-point Hitch Mount	
500 Low Profile	5.00 cu ft	Polyethylene	21" x 39" x 34"	75 lb w/mount	1/3 hp	2.63" x 6"	10"	Up to 30'	Salt	Vehicles with Class III hitch	Standard Class III Receiver Hitch Mount	
1000 Low Profile	8.00 cu ft	Polyethylene	19½" x 50½" x 35"	105 lb w/o mount	1/3 hp	2.63" x 6"	10"	Up to 30'	Salt	Full-Size Trucks (over 6,000 lb GVWR)	Optional Fixed Mount, Hitched Mount, Dual Swing Mount	
2500 Low Profile	8.50 cu ft	Polyethylene	25" x 50" x 42"	131 lb w/mount	1/3 hp	2.63" x 9"	15"	Up to 30'	Salt	Full-Size Trucks (over 6,000 lb GVWR)	Standard Class IV Hitch Mount	
LOW-PRO 300W Wireless	3.00 cu ft	Polyethylene	22" x 30" x 32"	68 lb	12-volt 1/3 hp	2½" x 5¾" Vertical High-Flow	10"	Up to 25'	Salt	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups	Standard 2" Receiver, Optional Drop Utility, Trailer Utility, 3-point Mounts	

WALK-BEHIND SPREADERS												
Model	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Approximate Weight (empty)	Spinner Size	Spreading Width	Materials					
WB-100B Broadcast Spreader	100 lb	Polyethylene	50" x 26" x 28"	25 lb	10"	Up to 20'	Bagged Ice Melters & Bagged Rock Salt					
WB-160D Drop-Style Spreader	160 lb	Polyethylene	48" x 38¼" x 36"	55 lb	—	3'	Bagged Ice Melters & Bagged Rock Salt					



Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

More jobs. Done faster. | [www.westernplows.com](http://www.westernplows.com) |



Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle rating with a spreader. This product is manufactured under the following US patents: 6,253,470; 6,422,490; 7,400,058; 7,737,576; CAN Patent 2,300,474. Western Products offers a limited warranty for all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: CONTRACTOR GRADE®, PRO-FLO™ 525, PRO-FLO™ 900, Striker™, Tornado™, Tornado LT™, WESTERN®.

©2015 Douglas Dynamics, LLC  
All rights reserved.

A DIVISION OF DOUGLAS DYNAMICS, LLC

Printed in U.S.A.  
Form No. 56853 – 6/15