



**PRO-FLO™ 525**

**PRO-FLO™ 900**

TAILGATE SPREADERS



---

**For precise ice control performance**, turn to the powerfully versatile PRO-FLO™ 525 and PRO-FLO™ 900 tailgate spreaders. A 2-stage, auger-fed delivery system and independent variable speed control provide consistent and efficient flow of all types of de-icing materials, including rock salt and sand. Designed to attach to a wide variety of vehicles, the PRO-FLO 525 and PRO-FLO 900 tailgate spreaders feature a corrosion-free poly hopper for long-lasting de-icing performance, making it the spreader of choice for any job site or surface condition.

---

PROVIDING THE ULTIMATE IN PRECISION PERFORMANCE AND VERSATILITY

## PRO-FLO™ 525

### 5.25 CU FT TAILGATE SPREADER

- Holds up to 420 lb of bagged or bulk de-icing material
- Comes standard with a combination 2" Receiver Hitch and 3-point Combo Mount.

## PRO-FLO™ 900

### 9.00 CU FT TAILGATE SPREADER

- Holds up to 720 lb of bagged or bulk de-icing material
- Available mounts include Pivot Mount, 2" Receiver Hitch (requires Adapter Mount) and 3-point Hitch Mount.  
*\*Mounts sold separately.*

### OTHER FEATURES

- Heavy-duty horizontal auger built of solid powder coated steel for strength and performance
- 10" nylon/glass reinforced resin (PRO-FLO™ 525) and 12" steel (PRO-FLO™ 900) spinners for a long, low-maintenance life
- Steel-rod top screen to break up chunks while loading for improved performance
- Molded polyethylene lid to protect material from the elements
- Standard vibrating inverted V to break up clumps and ensure smooth material flow



### VARIABLE SPEED CONTROL

Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Three standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the spreader is empty or when adjustments are needed, and LEDs make the control easy to read. Its compact size compared to traditional controls fits easily into today's modern truck cab designs.

### DUAL ELECTRIC MOTORS

Two instant-start, 12-volt electric motors provide quiet, reliable, independent control over the auger and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.

Model	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Approximate Weight (empty)	Electric Motor	Auger (Diam. x Length)	Spinner Size	Spreading Width	Materials	Vehicle Application	Available Mounts
PRO-FLO 525	5.25 cu ft (0.15 cu m)	Polyethylene	20½" x 38" x 34" (52.10 cm x 96.50 cm x 86.40 cm)	160 lb (72.6 kg)	Dual, 12-volt 1/3 hp	3" x 14" Heavy-Duty Solid Steel (7.62 cm x 35.56 cm)	10" (25.40 cm)	Up to 30' (Up to 9.14 m)	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, SUVs, 1-Ton or Smaller Pickups	Standard 2" Receiver, 3-point Combo Mount
PRO-FLO 900	9.00 cu ft (0.25 cu m)	Polyethylene	24" x 52" x 36" (60.90 cm x 132.10 cm x 91.40 cm)	180 lb (81.7 kg)	Dual, 12-volt 1/3 hp	3" x 20" Heavy-Duty Solid Steel (7.62 cm x 50.80 cm)	12" (30.50 cm)	Up to 40' (Up to 12.19 m)	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, 1-Ton or Smaller Pickups	Pivot Mount, 2" Receiver Hitch (requires Adapter Mount), 3-point Hitch Mount



Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

More jobs. Done faster. | [www.westernplows.com](http://www.westernplows.com) |



TWO WINTER WARRANTY

Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle rating with a spreader. This product is manufactured under the following US patent 6,253,470; 6,422,490; 7,400,058; 7,737,576; CAN patent 2,300,474. Western Products offers a limited warranty for all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: PRO-FLO™ 525, PRO-FLO™ 900, WESTERN®.